

## **AURA® 196 PRISMATIC REFLECTIVE SHEETING**

Brighter daytime appearance

Tiled prismatic optics for enhanced reflectivity

Durable fluorescent colors

Perfect for traffic or work zone signing

Exceeds many industry specifications



## POWERFUL 24-HOUR PERFORMANCE

The cellular construction of AURA® 196 Prismatic sheeting allows improved sign visibility 24 hours a day. AURA® 196 offers a brighter daytime color than many competitive products, and the tiled microprismatic optical elements provide enhanced retroreflectivity from multiple viewing angles. Further, the AURA® 196 Fluorescent Prismatic products provide improved daytime visibility even during low light conditions at dusk or dawn.



## AVAILABLE COLORS & INDUSTRY SPECIFICATIONS

AURA® 196 Prismatic is available in a variety of colors and configurations to meet many different industry requirements.



**Fluorescent Orange.** Construction work zone signs can be made more visible through the use of fluorescent orange sheeting. AURA® 196 Fluorescent Orange is available with adhesive options for both plastic or metal substrates. Exceeds many industry specifications, including ASTM D-4956 Type IX and Type IV, Mexico NCMT-05-03-001/13 Type B, and AASHTO M-268 Type B and Type C.



**Fluorescent Yellow Green.** Fluorescent yellow green signs create a high contrast against complex backgrounds to alert motorists to the presence of children or pedestrians. AURA® 196 Fluorescent Yellow Green exceeds the requirements of ASTM D-4956 Type IV, Mexico NCMT-05-03-001/13 Type A, and AASHTO M-268 Type B.



**Fluorescent Yellow.** Industry studies have shown that fluorescent yellow signs provide earlier sign detection compared with non-fluorescent signs. AURA® 196 Fluorescent Yellow can be used for warning signs or work zone signing applications as dictated by local signing specifications.



**Standard Colors.** In addition to the fluorescent colors, AURA® 196 Prismatic is available in white and yellow colors for manufacturing street name signs and a variety of regulatory and warning signs. Exceeds many industry requirements, including ASTM D-4956 Type IV, EN-12899-1 Class RA2, Mexico NCMT-05-03-001/13 Type A, and AASHTO M-268 Type B.